

HIGH TEMPERATURE FILTERS

HE-PP HT - 55



Description
Width A (mm)
Height B (mm)
Depth C (mm)
Media area (m²)
*Flow rate (m³/h)/
Delta P (Pa)*

M6 - ePM10 70%

HE-MP65A-HT	457	915	55	6,2	1800 / 30
HE-MP65A-HT	610	305	55	2,8	800 / 30
HE-MP65A-HT	610	610	55	5,9	1600 / 30

F8 - ePM2,5 75%


HE-MP95A-HT	457	915	55	6,2	1800 / 80
HE-MP95A-HT	610	305	55	2,8	800 / 80
HE-MP95A-HT	610	610	55	5,9	1600 / 80

* Energy Consumption, kWh/year: Calculated according to Eurovent Guideline 4/21-2018

** Energy class: according to Eurovent RS 4/C/001-2019



Tip Always position the spacers vertically!



APPLICATIONS

- Automotive industry and related component manufacturers
- Installations like Eisenmann, Dürr, Geico, etc.
- For use in filtration steps requiring a high temperature resistance
- For use in drying ovens, drying units or near heating units (make-up type)

ADVANTAGES

- Silicone free (approved by a large number of car manufacturers)
- High filtration area
- High efficiency
- Strong and high-finished execution

GENERAL FEATURES

- Efficiency following ISO 16890 : 2016
- Media: Deep pleat fiberglass paper
- Frame: Galvanized steel
- Sealant: Dynamic
- Separator: Aluminium
- Grids: Holding and protection on both air sides
- Final pressure drop: 450 Pa

HIGH TEMPERATURE FILTERS

HE-PP HT - 78




Barcode	Description	Width A (mm)	Height B (mm)	Depth C (mm)	Media area (m ²)	Flow rate (m ³ /h) / Delta P (Pa)
M6 - ePM10 70%						
HE-MP65A-HT	457 915	78	8,5	2600 / 100	3300 / 150	
HE-MP65A-HT	610 305	78	3,4	1180 / 100	1500 / 150	
HE-MP65A-HT	610 610	78	7,1	2360 / 100	2950 / 150	
F8 - ePM2,5 75%						
HE-MP95A-HT	457 915	78	8,5	2240 / 114	2800 / 150	
HE-MP95A-HT	610 305	78	3,4	1000 / 114	1250 / 150	
HE-MP95A-HT	610 610	78	7,1	2000 / 114	2500 / 150	

* Energy Consumption, kWh/year: Calculated according to Eurovent Guideline 4/21-2018

** Energy class: according to Eurovent RS 4/C/001-2019



Tip Always position the spacers vertically!



APPLICATIONS

- Automotive industry and related component manufacturers
- Installations like Eisenmann, Dürr, Geico, etc.
- For use in filtration steps requiring a high temperature resistance
- For use in drying ovens, drying units or near heating units (make-up type)

ADVANTAGES

- Silicone free (approved by a large number of car manufacturers)
- High filtration area
- High efficiency
- Strong and high-finished execution

GENERAL FEATURES

- Efficiency following ISO 16890 : 2016
- Media: Deep pleat fiberglass paper
- Frame: Galvanized steel
- Sealant: Dynamic
- Separator: Aluminium
- Grids: Holding and protection on both air sides
- Final pressure drop: 450 Pa